

DIVISION 1

GENERAL REQUIREMENTS

01045 CUTTING AND PATCHING

PART 1 – GENERAL

1.1 SUMMARY

- A. Cut and patch as required to repair damage as listed in the **Scope** and as specified herein:
 - Interior plaster or drywall
 - Stucco
 - Electrical, plumbing and HVAC openings
- B. Cut and patch with care to avoid damage to work, safety hazards, violation of warranty requirements, building code violations, or maintenance problems.
- C. When cutting and patching areas large enough to meet or exceed regulated thresholds, work shall be done in accordance with:
 - Painted or otherwise coated surfaces shall be done in accordance with [Section 01810 Lead Dust Hazards](#).
 - Asbestos or asbestos containing material shall be done in accordance with [Section 02080 Asbestos Removal](#).

PART 2 – MATERIALS AND PRODUCTS

2.1 MATERIALS

- A. Match existing materials with new materials so that patching work is consistent with surrounding surfaces.

PART 3 – EXECUTION

3.1 INSTALLATION

- A. Inspect field conditions to identify all work required.
- B. Perform work with workers skilled in the trades involved. Protect adjacent work from damage and dirt.
- C. If work will disturb painted or otherwise coated surfaces, install containment measures as outlined in [Section 01810 Lead Dust Hazards](#).
- D. If work will disturb asbestos or asbestos containing materials, install containment measures as outlined in [Section 02080 Asbestos Removal](#).
- E. For cutting work, use proper cutting tools, not chopping tools. Make neat holes. Check for concealed utilities and structure before cutting.
- F. Make patches, seams, and joints durable and consistent with adjacent surfaces.
- G. Clean work areas and areas affected by cutting and patching operations as outlined in [Section 01810 Lead Dust Hazards](#), [Section 02080 Asbestos Removal](#) and [Section 01800 Cleaning and Maintenance](#).

END OF SECTION – 01045 CUTTING AND PATCHING